

2SB1548, 2SB1548A

Silicon PNP epitaxial planar type

For power amplification


Complementary to 2SD2374 and 2SD2374A

Features

- High forward current transfer ratio h_{FE} which has satisfactory linearity
- Low collector to emitter saturation voltage $V_{CE(sat)}$
- Full-pack package which can be installed to the heat sink with one screw

Absolute Maximum Ratings ($T_C=25^\circ\text{C}$)

Parameter		Symbol	Ratings	Unit
Collector to base voltage	2SB1548	V_{CBO}	-60	V
	2SB1548A		-80	
Collector to emitter voltage	2SB1548	V_{CEO}	-60	V
	2SB1548A		-80	
Emitter to base voltage		V_{EBO}	-5	V
Peak collector current		I_{CP}	-5	A
Collector current		I_C	-3	A
Collector power dissipation	$T_C=25^\circ\text{C}$	P_C	25	W
	$T_a=25^\circ\text{C}$		2	
Junction temperature		T_j	150	$^\circ\text{C}$
Storage temperature		T_{stg}	-55 to +150	$^\circ\text{C}$



Electrical Characteristics ($T_C=25^\circ\text{C}$)

Parameter		Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	2SB1548	I_{CES}	$V_{CE} = -60\text{V}, V_{BE} = 0$			-200	μA
	2SB1548A		$V_{CE} = -80\text{V}, V_{BE} = 0$			-200	
Collector cutoff current	2SB1548	I_{CEO}	$V_{CE} = -30\text{V}, I_B = 0$			-300	μA
	2SB1548A		$V_{CE} = -60\text{V}, I_B = 0$			-300	
Emitter cutoff current		I_{EBO}	$V_{EB} = -5\text{V}, I_C = 0$			-1	mA
Collector to emitter voltage	2SB1548	V_{CEO}	$I_C = -30\text{mA}, I_B = 0$	-60			V
	2SB1548A			-80			
Forward current transfer ratio		h_{FE1}^*	$V_{CE} = -4\text{V}, I_C = -1\text{A}$	70		250	
		h_{FE2}	$V_{CE} = -4\text{V}, I_C = -3\text{A}$	10			
Base to emitter voltage		V_{BE}	$V_{CE} = -4\text{V}, I_C = -3\text{A}$			-1.8	V
Collector to emitter saturation voltage		$V_{CE(sat)}$	$I_C = -3\text{A}, I_B = -0.375\text{A}$			-1.2	V
Transition frequency		f_T	$V_{CE} = -10\text{V}, I_C = -0.5\text{A}, f = 10\text{MHz}$		30		MHz
Turn-on time		t_{on}	$I_C = -1\text{A}, I_{B1} = -0.1\text{A}, I_{B2} = 0.1\text{A}$		0.5		μs
Storage time		t_{stg}			1.2		μs
Fall time		t_f			0.3		μs

* h_{FE1} Rank classification

Rank	Q	P
h_{FE1}	70 to 150	120 to 250

Note: Ordering can be made by the common rank (PQ rank $h_{FE1} = 70$ to 250) in the rank classification.

